

PHOTO TEMPLATE FOR PAVEMENT EVALUATION

INSTRUCTIONS:

The first evaluation should be performed at the beginning of the project limits, with subsequent evaluations occurring at a uniform distance each 1/8 mile (660 feet) along the roadway until reaching the other end of the limits. If the project is less than 3/8 mile (1,980 feet), conduct three evaluations at a uniform distance (e.g., a 1/4-mile project would include three evaluations, spaced 440' apart). If the project is greater than one mile in length, conduct at least eight evaluations at a uniform distance (e.g., a 1 ½ mile project would include eight evaluations, spaced 990' apart).

Record the PASER rating for each location in the table below. Individual location ratings must be whole numbers. If multiple roadways are within the project limits, simply list the new roadway name in the column on the left. You may attach another sheet with additional locations if needed. Fill out an evaluation sheet for each location (see next pages), a picture of each location, and a map showing all evaluation locations. Each location photo should show the entire width of the roadway, from curb to curb. Photos can be taken from the side of the roadway or standing in the middle. See Asphalt PASER manual, pages 16-25, for examples.

PHOTO/LOCATION #1

PHOTO/LOCATION #2

PHOTO/LOCATION #3

PHOTO/LOCATION #4

PHOTO/LOCATION #5

PHOTO/LOCATION #6

PHOTO/LOCATION #7

PHOTO/LOCATION #8